

ValueSpec is an advocacy of NELTEX to encourage Designers, Developers & Stakeholders to place Value in their Specifications. The notion is: "To get the right Quality, everyone must place Value on Specification Writing."

SANIGUARD 8055 Specifications

Sanitary Pipes	Conform to ASTM D2729 80 Joules Izod Impact and 55 MPa Tensile Strength
Sanitary Fittings	Conform to ASTM D3311
Composition	Made with 90% K65 Resin by Mass
Jointing	Socket Type: Use only Neltex PVC Pipe cement
Toxicity	Pipes to be Heavy Metal-Free (HMF) as validated through Inductively Coupled Plasma Optical Emission Spectrometry (ICP OES) method. (Mercury, Cadmium, Tin & Lead must not be present)
Markings	Pipes to be marked using Continuous Ink Jet (CIJ) Printing Method With traceability codes

SANIGUARD PIPES

SANIGUARD 1000

SANIGUARD S600

ND	DN	Min. Pipe Thickness	ND	DN	Min. Pipe Thickness
2"	57 mm	2.54 mm	2"	57 mm	1.85 mm
3"	82 mm	3.70 mm	3"	82 mm	2.54 mm
4"	107 mm	3.81 mm	4"	107 mm	2.54 mm

SANITARY FITTINGS

ELBOW

WYE & TEE

ND	DN	ND	DN
2" x 90°	57 mm x 90°	2 x 2"	57 mm x 57 mm
3" x 90°	82 mm x 90°	3 x 3"	82 mm x 82 mm
4" x 90°	107 mm x 90°	3 x 2"	82 mm x 57 mm
2" x 45°	57 mm x 45°	4 x 4"	107 mm x 107 mm
3" x 45°	82 mm x 45°	4 x 3"	107 mm x 82 mm
4" x 45°	107 mm x 45°	4 x 2"	107 mm x 57 mm

CLEAN-OUT SET

BUSHING REDUCER

ND	DN	ND	DN
2"	57 mm	4 x 3"	107 mm x 82 mm
3"	82 mm	4 x 2"	107 mm x 57 mm
4"	107 mm	3 x 2"	82 mm x 57 mm


COUPLING

P-TRAP

ND	DN	ND	DN
2"	57 mm	2"	57 mm (With Clean-out)
3"	82 mm	3"	82 mm
4"	107 mm	4"	107 mm



For over 5 decades now, Neltex has been the preferred and trusted brand for total piping solutions. With its commitment to constant innovation and sustainable construction that makes it the gold standard for quality and project specifications, and now with Asia's biggest Lead-Free PVC Manufacturing plant (producing 30,000 MT annually), Neltex continues to be the PVC Pipe brand behind brilliance in construction.



Neltex Development Company, Inc. 26th Floor, Unit A,
Washington Tower, Asiaworld City, Tambo Paranaque
Tel. No: (02) 879 - 7777
Fax No: (02) 879- 3777

Visit our website and facebook page:

www.neltex.com

www.facebook.com/neltexpipes



Behind every
Brilliant Design

NELTEX

SANIGUARD 8055

Behind Brilliance

BEHIND GUARD DWV TOUGH PIPE

SANIGUARD 8055
is IMPACT MODIFIED



NELTEX GUARD DWV Pipes have a unique PVC DNA making it the toughest in its class (80 Joules Izod Impact and 55 MPa Tensile strength). This guarantees that GUARD DWV Pipes can last not only the design life of your building; they can also withstand the rough and tumble of the jobsite.

SANIGUARD S600
can do the job of other brands' S1000!

NELTEX Guard DWV Pipes are designed to be brilliantly tough such that the SANIGUARD S600 can withstand S1000 standards. This unique GUARD DWV feature allows Developers and Contractors to save up to 25%!

This unique Product Benefit of the Guard DWV was showcased in the NELTEX HATAW CHALLENGE as witnessed by more than 5,000 PALO-ers. Product Test Certificate to show SANIGUARD S600 passing S1000 standards are available upon request.



BRILLIANCE of GUARD FITTINGS:

SANIGUARD 8055 Fittings
are PIPE TOUGH

Guard DWV Fittings are the only PVC Sanitary Fitting System that is injection Molded out of K65 PVC Resin. This means that whenever you use GUARD DWV Pipes & Fittings, you can be sure of system integrity as the PVC Fittings are made from the same materials that the PVC Pipes are made of.



ONLY SANIGUARD 8055 Fittings
Follow **ASTM D3311 Fitting Standards**

BRAND X



BRAND Y



Only GUARD DWV Fittings conform to ASTM D3311. Fittings each have the right sweep slopes and bends to ensure transport accuracy and smooth waste water flow.

To get the full benefit of having a world class DWV Pipe System, specify only GUARD DWV Pipes & Fittings.

NELTEX
SANIGUARD 8055